

Exchange of engineering data for communication systems based on AutomationML using an EtherNet/IP<sup>TM</sup> example

Dipl.-Wirtsch.-Ing. Falko Bendik Otto-von-Guericke-University Magdeburg

October 14, 2015



MECHANICAL ENGINEERING



# Overview

- Motivation
- Requirement Analysis
- Overview of AutomationML
- General communication system modeling methodology in combination with EtherNet/IP<sup>™</sup> example




### Requirements on the engineering of production systems

- complexity of the systems
- amount of data to be handled
- high development costs
- different applicable efficient engineering processes
- different sets of software tools in the development process
- exploiting different engineering artifacts
- modular control structures / distributed control systems




Involved engineering activities exchanging engineering artefacts





### General semantic for communication systems with AutomationML

- A significant cost factor of industrial plants is the engineering process.
- To reduce this factor new methods and description tools are needed!




- Project management (3%)
- Pre-commissioning (2%)
- Assembly (11%)
- Bought-in parts (28%)
- Geometry simulation (1%)
- Robot programming offline/online (5%)
- Engineering [incl. Commissioning] (50%)




### Where are the avoidable costs exactly?

- A survey reveals:
- □ That 82% of the respondents cannot exclude non-redundancy of planning steps.
- □ That the pdf/paper interface is the most widespread interface with 31%.
- □ That only 12% of the respondents use standardized interfaces.

### Do redundancies exist in the engineering process?



Which interfaces are currently used?





### Solutions for an efficient engineering of production systems

- highly sophisticated engineering tools
- fault free creation of engineering artifacts
- consistent exchange of engineering data
  - planning of communication systems, addressing and communication package structure
- device configuration data and structures describing the communication network
- contain topological information
- information on communication links and their quality
- basic semantic libraries and process models of communication models




# Logical and physical topology of communication systems

### Logical modeling

 addressing of applications and the expected transmission rate of information between application parts

### **Physical modeling**

 physical communication links between devices





#### What is needed?

- identify types of information characterizing a communication system
- which information should be covered by a method for a neutral exchange of communication system engineering information
- data in the engineering process of a production system
  - □ mechanical and electrical engineering data
  - □ control programming "PLC Code"
  - □ virtual commissioning
  - □ commissioning
- definition of involved automation devices and their wiring
- control programming, runtime information (represented by control variables)
- identify additional technical details such as data types, transmission rates etc.



#### What is used?

- electrical engineering: specifying wiring diagrams, wiring
- control programming: specify device configurations, variable lists, link descriptions
- virtual commissioning: used to test the physical realization of the intended data exchange
- commissioning: used variable declaration and linking descriptions for monitoring and diagnosis





### What information is needed to describe the modeling method?

- control application
  - □ components are linked with each other by exchanging variables
  - □ need to establish logical connections by logical interfaces (namely the corresponding exchanged variables or sets of them)
  - □ identify the requirements in terms of communication properties on the exchange of data within the logical connections
  - □ create properties of the control application components, e.g. processing times, characteristics of logical interfaces, or a port number



### What information is needed to describe the modeling method?

- control devices
  - □ control application components are running on different physical devices
  - □ the logical connections must be realized by the physical data exchange
  - physical device has interfaces for physical connections (necessary cables for communication system realization)
  - describe the active and passive infrastructure components such as switches, interface converters, plug, or cable types
  - □ analogy to the control application parts, the logical connections, and the logical interfaces
  - represent the properties of the physical devices, the physical interfaces and the physical links




### What information is needed to describe the modeling method?

- general modeling requirements
  - □ represent the relations between logical and physical connections
  - □ map the corresponding structures at least at the used interfaces to each other
  - □ communication system information is transmitted by data packages
  - represent the mapping of variables within the data package sender to variables within the data package receiver




- AutomationML is a XML based data format.
- It is an international standard (IEC 62714)
   and free of charge
- AutomationML allows a consistent data exchange within different tool chains
- It allows the integration of the world of tools into the digital factory of the future





### Which data contents are covered by AutomationML?





### AutomationML is ...

- Data format, that allows a data exchange of engineering data of production systems independent of the manufacturer.
- Storage format for information.
- Connection between different discipline-specific engineering tools with that it is usable in the whole engineering process.
- Object orientated and allows the modeling of plant components as data objects summarizing different aspects.
- Combination and adaptation of already existing industry formats that were developed for exchange and storage of different engineering aspects.
- consistent, distributed document architecture, that enables the handling of large amounts of data and the outsourcing of libraries to external documents.




### AutomationML is NOT...

- Tool functionality
- Review of conditions, attribute values, relations, references, or semantic correctness of several data objects
- Review and matching of the consistence resp. version of data objects
- Automatic standardization of user specific information
- Automatic creation of libraries
- Automatic management of versions and variants
- Project management tool
- Project management database
- ▶ But it allows the storage of all data required for that




### The AutomationML - architecture

- Based on the use of existing XML data formats
- □ CAEX structure/relation of the plant objects
- □ COLLADA geometry and kinematics
- □ PLCopen XML behavior










# Application process






### **Topology description with CAEX**

- Definition of the meaning of objects by roles
- Definition of reusable objects for the engineering
  - □ Components
  - □ Interfaces
  - □ Roles
- Representation of project data as project tree
- Integration of object descriptions as attributes
- Relations between objects and references to external documents


# Overview of AutomationML






# Topology description with CAEX

# Overview of AutomationML





### Topology example




# **Project**






### Geometry and kinematic description with COLLADA

- COLLADA is standardized as ISO/PAS 17506
   □ KHRONOS
- Originally developed for the gaming industry
  - □ Main driver: Sony








### Behavior description with PLCopen XML

- PLCopen XML based on IEC 61131-3
- Derived from the SPS world


 Allows the description of conduct about different types of models like Gantt Charts, PERT Charts, Impuls diagram, State Charts, ...





### Networks are the integral part of modern communication systems

- Combination of used elements
- Requirement: Illustration of
  - □ Logical network structures at application level
  - Physical network structures for the technical realization of interactions
  - □ Relationship between both views
  - □ Descriptive attributes of both views





### Example network with EtherNet/IP™

0. Application of predefined basic libraries

TOIES

PhysicalDevice {Class: AutomationMLBaseRole}

Role PhysicalPortList {Class: AutomationMLBaseRole}

Role PhysicalConnection {Class: AutomationMLBaseRole}

Role PhysicalNetwork {Class: AutomationMLBaseRole}

Role LogicalDevice {Class: AutomationMLBaseRole}

Role LogicalPortList {Class: AutomationMLBaseRole}

Role LogicalPortList {Class: AutomationMLBaseRole}


Role LogicalConnection {Class: AutomationMLBaseRole}

Role LogicalNetwork {Class: AutomationMLBaseRole}

Role LogicalNetwork {Class: AutomationMLBaseRole}

PhysicalEndPoint {Class: Communication}


LogicalEndPoint {Class: Communication}





### **Example network with EtherNet/IP™**


- 1. Definition of the role classes for the corresponding use case
  - ➤ RoleClassLib





### **Example network with EtherNet/IP™**

- 2. Definition of the interfaces for the corresponding use case
  - ► InterfaceClassLib



AutomationMLInterfaceClassLib



### Example network with EtherNet/IP™ (Part 1&Part 2)

- 3. Modeling of the used devices and connections
  - ➤ SystemUnitClassLib
- SIT EthernetiPCommunicationPackage { Class: }

   SIT EthernetiPExpliciteMessagePackage { Class: EthernetiPCommunicationPackage} 

   SIT GetSingleAttributeRequest { Class: EthernetiPExpliciteMessagePackage} 

   SIT GetSingleAttributeResponce { Class: EthernetiPExpliciteMessagePackage} 

  SIT SupportedRoleClass: EthernetiPRoleClassLib/EthernetiPCommunicationPackage/EthernetiPExpliciteMessagePackage 

  SIT SupportedRoleClass: EthernetiPRoleClassLib/EthernetiPCommunicationPackage 

   SIT EthernetiPObjects { Class: }

   SIT EthernetiPobjects { Class: Identity Object} 

  SIT CommunicationObjectInstanceAttribute { Class: }

  SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassAttribute { Class: }

   SIT CommunicationObjectClassEthernetiPObjects}

   SIT CommunicationObject { Class: EthernetiPObjects}

   SIT Assembly Object { Class: EthernetiPObjects}

   SIT Assembly Object { Class: }
- ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   ✓ 
   EthernetIPSClientResponceVelocity { Class: EthernetIPServerResponce} Rotation {Class: VariableInterface} SupportedRoleClass: EthernetIPRoleClassLib/EthernetIPPhysicalDevice SIT EtherNetIPExpliciteMessagingEcoderProfileVelocity { Class: } EthernetIPClientRequest { Class: EthernetIPClientRequest} EthernetIPServerResponce {Class: EthernetIPServerResponce} EthernetIPEncoderProfileVelocityResponce { Class: EthernetIPEncoderProfileVelocityResponce Role: } SupportedRoleClass: EthernetIPRoleClassLib/EthernetIPCommunicationPackage 🛕 😋 Interfaces EthernetIPDatagrammObject { Class: EthernetIPDatagrammObject} EthernetIPEncoderProfileVelocityRequest { Class: EthernetIPEncoderProfileVelocityRequest Role: } SupportedRoleClass: EthernetIPRoleClassLib/EthernetIPCommunicationPackage 🛕 👥 Interfaces EthernetIPDatagrammObject { Class: EthernetIPDatagrammObject} SupportedRoleClass: EthernetIPRoleClassLib/EthernetIPLogicalConnection Suc EthernetIPEncoderProfileVelocityRequest {Class:} Sur EthernetIPEncoderProfileVelocityResponce { Class: }




3. Modeling of the used devices and connections


Example network with EtherNet/IP™ (Part 3)

➤ SystemUnitClassLib






# General communication system modeling methodology





### **Example network with EtherNet/IP™**

- 4. Modeling of the system
  - ► InstanceHierarchy






IO Device

Communication

**Application to communication** 


network




PLC



### **Determination of the semantics for several attributes**






```
<InstanceHierarchy Name="ExampleIH">
  <InternalElement Name="AutomationMLObject" ID="de88f618-6802-40cc-9dd3-2d73546e6280">
     <a href="Attribute Name="length" AttributeDataType="xs:integer" Unit="mm">
       <Description>Attribute with an eCl@ss RefSemantic</Description>
       <DefaultValue>5</DefaultValue>
       <Value>5</Value>
       <RefSemantic CorrespondingAttributePath="ECLASS:0173-1#02-BAA018#004" />
     </Attribute>
     <a href="minSize" AttributeDataType="xs:string" Unit="mm">
       <Description>Attribute with an eCl@ss RefSemantic</Description>
       <DefaultValue>10</DefaultValue>
       <Value>10</Value>
       <RefSemantic CorrespondingAttributePath="ECLASS:0173-1#02-BAE496#005" />
     </Attribute>
  InternalElement>
InstanceHierarchy>
```



# Summary

### **Summary**

- neutral data format
- system models / engineering of automation technology
- fault free creation of engineering artifacts
- modelling industrial communications
- basic semantic libraries
- decrease of planning costs









FACULTY OF MECHANICAL ENGINEERING

### **THANK YOU**