Definition and Legend

This document tracks changes made in the specifications that are mandatory for products implementing the technologies. ODVA publishes this list separately from the specifications in order to give developers and managers advanced notice of changes that will impact the products for which they are responsible. This document does not list any optional changes. For optional changes and enhancements, see the Revision page at the front of each specification volume.

Scope of Change

O: Optional: An optional feature/function C: Conditional: An optional feature/function that is required under specific conditions, see specification M: Mandatory: A feature/function that is required If the Scope of Change differs between Descriptions of a single spec change, separate rows are shown.

Scope of Products Impacted

New: Products taking the conformance test the first time Existing: Products that already have a valid DOC and are being updated with new featues, as defined in section 8 of the Conformance Policy (PUB00008)

The effective date is the date when the change will be enforced by conformance testing. Specification volumes are referenced by number. The titles of the volumes can be found on a tab in this spreadsheet. If there is a discrepancy between this spreadsheet and the specification, the latest released specification(s) will prevail. The title of each page identifies the the publication cyle of the changes shown. There are two publication update cycles each year, typically in April and November.

Updated December 4, 2023

Volume Number	Volume Title	Edition at November 2023 (2023 PC 2) Publication
1	The Common Industrial Protocol	3.35
2	EtherNet/IP Adaptation of CIP	1.33
3	DeviceNet Adaptation of CIP	1.16
4	ControlNet Adaptation of CIP	1.09
5	CIP Safety	2.25
6	CompoNet Adaptation of CIP	1.08
7A	Integration of Modbus Devices into the CIP Architecture	1.12
7B	Integration of HART Devices into the CIP Architecture	1.03
7C	Integration of IO-Link Devices into the CIP Architecture	1.05
8	CIP Security	1.17
9	CIP Motion	1.11

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Expand States Protected by CIP Security	8	1.17	 Changes to security objects containing CIP Security configuration shall only be accepted when sent over a CIP Security connection even if the device is in the Factory Default state. (Section 4-3.1.3) Changes to security related objects without containing CIP Security configuration shall be made over a CIP Security connection once the CIP Security Object in not in the Factory Default state. (Section 4-3.1.3) 	New and Existing	С	Nov-23	Apr-25
Update Originator Cipher Suite Requirements	8	1.17	Cipher suits required for a given profile applies to a device implementing that profile, no matter it is a Target or Originator. (Table 3-5.4 and Table 3-5.5)	New and Exsiting	с	Nov-23	Nov-23
IANA Port Admin EDS Keyword	2	133	[IANA_Port_Admin] entry is required if a a device supports TCP/IP Interface Object's instance attribute 14 (IANA Port Admin), otherwise not allowed. (Table 7-7.1).	New	С	Nov-23	Apr-25
EthernetIP Usage Profile Updates	2		 EtherNet/IP Usage Profiles was updated to allow a device support multiple usage profiles. (Table 11-3.1). The EtherNet/IP Capability Item in the ListIdentity response shall only set bits corresponding to the features supported on the interface receiving the request, not all the interfaces supported by the device. (Table 2-4.5) 	New	C	Nov-23	Nov-23
Modbus Serial Link Object Clarification	7A		 Data Bits and Stop Bits of Modbus Serial Link Object instance attribute 3 shall be encoded as binary not ASCII. (Table 5-6.10) Modbus Serial Link Object bumped to Revision 2. (Table 5-6.1) 	New and Existing	С	Nov-23	Nov-23
Identity object Protection Mode attribute	7C	1.05	Identity Object Protection Mode attribute 19 is now allowed for Virtual IO-Link device. (Table 5-1.1)	New and Existing	С	Nov-23	Nov-23

Scope of Products Scope of Publish Effective Topic Volume Edition Description Impacted Change Date Date 1. Introduce Concurrent Connections functionality to the CIP specification (Section 3-7). 2. Add new services and attributes to Connection Manager Object to handle Concurrent Connections, bump the object revision to 02 (Table 3-5.1 and 3-5.8). Concurrent Connections 1 3.34 3. Define new Connection Path rules for Concurrent Connections (Section 3-5.5.1.10, Appendix C-1.4.3.6.2). New С Apr-23 Apr-23 A. Describe new CIP Routing behavior for Concurrent Connections (Section 10-2.2). 5. Add new entries to [Connection Manager] section in EDS file (Table 7-3.49). 6. Concurrent Connections packets use CRC to protect the integrity of packets (Appendix C-7). 1. Introduce revision concept to Device Profile definition (Table 6-2.2). 2. Add a Supported Device Type Revision attribute 38 to Identity Object and bump its revision to 03 (Table 5A-3.34 Device Type Revision 1 New С Apr-23 Apr-23 2.1 and 5A-2.3) 3. Add new entry to [Identity Object] section in EDS file. 1. Add Process Measurement Value Object and Process Totalized Value Object for process field devices Supporting Objects for Process Device 1 С 3.34 (Section 5B-21 and 5B-22) New Apr-23 Apr-23 Profiles . Add new object class sections for these objects in EZ-EDS (Table 7-3.4). Add three new Process Device Profiles: Coriolis Flow Device, Electromagnetic Flow Device and Vortex Flow С Flow Process Device Profile 1 3.34 New Apr-23 Apr-23 Device (Table 6-5.1 and 6-5.2). **Requirements for Process Device Profiles** 1 3.34 Specify requirements for Process Device Profiles (Section 6-2.5). New С Apr-23 Apr-23 Add two new Process Device Profiles: Scaled Pressure Device and Standard Pressure Device (Table 6-5.1 and 6-Pressure Process Device Profile 1 3.34 New С Apr-23 Apr-23 5.2) Process Device Diagnostics Simulation 1 3.34 Update Process Device Diagnostics Object Revision to 4 (Table 5B-19.5) New and Existing С Apr-23 Apr-23 Addition Devices not implementing LLDP Reception are not allowed to support LLDP Data Store attribute 4 and Last 2 LLDP Reception Clarification New and Existing 1.32 Μ Apr-23 Apr-23 hange attribute 5 of LLDP Management Object. 1. Clarify that data in LLDP frames is sent in big-endian format. Deprecate the CIP Identification TLV with subtype 1 and create a new CIP Identification TLV with subtype 9 that is clearly specified as big endian (Section LLDP Clarifications 2 1.32 9-8.3). New and Existing С Nov-24 Apr-23 2. Make it possible for devices to support both the LLDP Date Table Object and SNMP at the same time (Table 5 15.3). 2 New and Existing С Nov-23 PRP-HSR Updates 1.32 Add additional attribute 21 necessary to conform to the latest IEC 62439-3 standard for HSR. Apr-23 7C С Improve error reporting 1.04 Use object specific general status code to return IO-Link command errors (Table 5-3.4, 5-3.8 and 5-3.10). New Apr-23 Apr-23 7C 1.04 Use 0x10000 as the instance value for accessing Index 0 in IO-Link Service Parameter Object (Section 5-3). New and Existing С Apr-23 Apr-23 Support access to Index 0 Change the conversion of an OctetStringT to an array of USINT instead of previous SHORT STRING (Table C-OctetStringT conversion 7C 1.04 New and Existing С Apr-23 Apr-23 3.1) 7C 1.04 Change the Conversion Type value of an ArrayT to allow for 2 byte conversion types. (Table C-3.1). New С Apr-23 ArravT conversion Apr-23 7C С RecordT conversion type 1.04 Add a conversion type for the IO-Link RecordT data type(Table C-3.1). New and Existing Apr-23 Apr-23 7C New and Existing С Apr-23 TimeT STIME conversion 1.04 The convertion between TimeT to STIME needs to use new constant (Appendix C-3.1.1) Apr-23 IO-Link Service Parameter object Device Add Device State Conflict (0x10) and new Extended Status codes to IO-Link Service Parameter object service 7C С 1.04 New Apr-23 Apr-23 State conflict extended status responses (Table 5-3.3 - 5-3.12). EtherNet/IP Security Object Revision bumps to 8, add a new Required PSK Usages Supported Class attribute Expand PSK USage Field 8 1.16 New and Existing С Apr-23 Apr-24 Table 5-4.2 and section 5-4.3.2). Member Services for PSK Attribute 8 1.16 Member services are required for Resource-Constrained CIP Security Profiles, optional for others (Table 5-4.6). New and Existing С Apr-23 Nov-24 8 Make several previously required cipher suites to recommended (Table 3-5.4 and 3-5.5). New and Existing С Apr-23 Apr-23 Cipher Suite Requirements 1.16

PSK Usage Clarification	8	1.16	Disallow multiple PSKs from being set that re-use a given identity value (Section 5-4.4.5).	New and Existing	С	Apr-23	Nov-23
Certificate handling	8	1.16	CIP Security devices are required to support at least two dynamic instances of the Certificate Management Object (Section 5-5.1.1). CMO Revision becomes 2, Class attribute 2 and 3 are required now. Devices that already passed the conformance test and only support one dynamic instance may continue using just one dynamic instance. This will degrade the interoperability and robustness in systems, but it is recognized that devices might not have the resources to implement this change.	New and Existing	С	Apr-23	Nov-23
Consumer Activity Monitor Usage Clarification	5	2.25	Add text in FRS78 indicating that the Consumer Activity Monitor timer should be reset to the remaining data age based on the last reception time stamp (Section 2-1.8.3.1, F-3.8.5, F-3.9.2.3).	New and Existing	С	Apr-23	Apr-23
Tst52 Split	5	2 2 5	Split TST52 into four tests of TST132, TST133, TST134 and TST135 (Appendix F-2.6.2, Table F-3.11.5.2.1, F- 3.11.5.2.4, F-5.1).	New	С	Apr-23	Apr-23

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Enumeration for String Data Types	1	3.33	Any Param entry whose type is string (STRING, STRING2 or SHORT_STRING) can also be enumerated using the Enum Keyword in addition to integer and bit string. (Section 7-3.6.6.2 and Table 7-3.26)	New	М	Nov-22	Nov-22
LLDP SNMP MIB	2	1.31	Added requirements and reference for ODVA devices implementing the SNMP LLDP MIB. (Section 9-8.1) (https://www.odva.org/subscriptions-services/additional-tools/request-lldp-management-information-base)	New and Existing	С	Nov-22	Apr-23
Safety Reset Type2 Clarification	5	2.24	Changed Soft-set MacID to Soft-set NodeID, Soft-set Baud Rate to Soft-set Communication Link Parameters (Table 5-4.21)	New and Existing	С	Nov-22	Apr-24
TST130 Adding Running Conditions	5	2.24	Added running conditions for TST130. (Appendix F-5.1)	New	М	Nov-22	Nov-22
Correct Reset Factory settings command code	7C	1.3	Identity Object Type 1 Reset shall cause IO-Link Master issue Restore factory setting command 0x82 (not 0x81) to the IO-Link Device. (Table 5-2.6)	New and Existing	М	Nov-22	Nov-22
Ingress Egress Object	8	1.15	 Added a new CIP Security Profile: Device-Based Firewall Profile (Table 8-1.1 and Section 8-2.1) Added new Ingress Egress Object which is required by Device-Based Firewall Profile(Section 5-9) Added Available Originator Cipher Suites and Allowed Originator Cipher Suites attributes to EtherNet/IP Security Object (Table 5-4.3) 	New	С	Nov-22	Apr-24
Correct EIPSO Reset Condition	8	1.15	EtherNet/IP Security Object Reset service will be accepted over any connection up until the CIP Security Object's state attribute transitions to Configured, at which point this Reset will only be accepted over a CIP Security connection. (Table 5-4.5.1)	New and Existing	Μ	Nov-22	Nov-22
Make Wildcards Optional for SAN with Hostname	8	1.15	IP Address must be supported in SAN, Hostname and URI support in SAN are optional. (Section 5-4.4.17)	New and Existing	М	Nov-22	Nov-22

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Product Authenticity Check	1	3.32	Added an Optional Product Identity Certificate attribute 39 (Table 5A-2.3) and a Conditional Certificate_Challenge service (Table 5A-2.18) to Identity Object.	New and Existing	С	Apr-22	Apr-22
Register Object Data Access Rule Clarification	1	3.32	Clarify Register Object Direction and Size attributes are NV attributes, also clarify the Set are Optional for attribute 2-4. (Table 5A-2.2)	New and Existing	С	Apr-22	Apr-22
Improve LLDP alignment with IEEE 802.1AB-2016	2	1.30	LLDP Specification was updated to align with IEEE 802.1AB-2016: 1. For LLDP Enable attribute 1 of LLDP Management Object, on set of Global Enable Bit 0 from 1 to 0, all existing table entries shall be removed. (Table 5-15.4) 2. LLDP Management Object msgTxInterval attribute 2 valid range was changed. Last Change attribute 5 meaning was changed. (Table 5-15.3) 3. The meaning of LLDP Data Table Object Last Change attribute 9 was changed. (Table 5-16.3) 4. Added LLDP Link State Transition requirements (Section 9-8.6)	New and Existing	С	Apr-22	Apr-22
SAN Formatting Clarification	8	1.14	Clarify that only DNS Name, IP Address and Uniform Resource Identifier (URI) must be supported in Subject Alternative Name (SAN) within CIP Security certificates. (Section 5-5.7.1)	New and Existing	С	Apr-22	Apr-22
CRL Clarification	8	1.14	 The EtherNet/IP Security Object Certificate Revocation List attribute 8 now can hold an Array of CRLs rather than a single CRL and the object revision was bumped to 7. (Table 5-4.3) Clarify that a certificate may only be revoked by the Certificate Authority which originally signed it. (Section 5-4.4.8) Two kinds of GAA Format: one for Revision 1-6; another for Revision 7 and onward. (Table 5-4.11) 	New and Existing	С	Apr-22	Nov-23
Send Receive Fragment Requirement Date	8	1.14	The requirement of supporting Send_Receive_Fragment service was extended to November 2022.	New and Existing	С	Apr-22	Apr-22

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Find Next Object Instance Service Clarification	1	3.31	Clarify that Find_Next_object_Instance service is not supported at the instance level, even though the Instance ID value to use as the lower bound of the search is provided in the application path. (Appedix A-4.14)	New and Existing	С	Nov-21	Nov-21
Clarify Protection Mode	1	3.31	CIP Security devices are required to allow certain authenticated requests while in Explicit and/or Implicit Protection mode. (Section 5A-2.3.1.16.1, Vol 8 section 5-2)	New and Existing	с	Nov-21	Nov-21
File Object Download Transfer Clarification	1	3.31	 Removed the summary text in Section 5A-42.5.6 to eliminate the redundancy and conflicit to Table 5A-42.26. Did the same change to previous revision of File Object which is listed in Appendix E-2.5.6. 	New and Existing	С	Nov-21	Nov-21
Set Access Rule Clarification 2021	1	3.31	An attribute with Settable (Set) Access rule shall be accessed by at least one of the set services. (Section 4-4.1)	New and Existing	С	Nov-21	Nov-21
Cipher Suite Changes	8	1.13	 Require GCM-based cipher suites be supported and change RSA-based cipher from required to optional for CIP Security endpoints. (Table 3-5.4 Section 5-4.4.6 and 5-4.9) EtherNet/IP Security Object Allowed Cipher Suites attribute 4 shall only allow cipher suites that support confidentiality in the Factory Default state. PSK based cipher suites shall not be allowed by default. (Section 4- 4.4) 	New and Existing	C	Nov-21	Apr-23
Conditional Support for Security Profiles Configured	8	1.13	Support for Security Profiles Configured attribute 3 of CIP Security Object will be required starting from April 2022.	New	С	Nov-21	Apr-22
Pull Model Profile	8	1.13	 Added a new EtherNet/IP Pull Mode Profile for devices supporting Pull Model.(Table 1-3.1)(Table 5-3.5) All CIP Security devices must support Push model and optionally support Pull model. For devices supporting both mechanism, the Pull Model is the default mechanism for obtaining a certificate. (Section 4-3.4.1) 	New and Existing	С	Nov-21	Nov-21
PSK Usage Field	8	1.13	Added PSK Usage field to the Pre-Shared Keys attribute 5 of EtherNet/IP Security Object which brings EtherNet/IP Security Object to Revision 7. (Table 5-4.2 and Table 5-4.3)	New and Existing	С	Nov-21	Apr-23
SAN Update	8	1.13	Check Subject Alternative Name attribute 17 of EtherNet/IP Security Object is optional for device with originator funcationality. It must not be implemented by devices without originator capabilites. (Table 5-4.3)	New and Existing	с	Nov-21	Nov-21
Make Certificate Signing Request Attributes (csrattrs) Optional	8	1.13	Requesting csrattrs to the EST server during configuration of Pull Model is changed from required to optional. (Section 4-3.4)	New and Existing	0	Nov-21	Nov-21
Prevent DTLS Timeout Disable	8	1.13	Removed the ability to disable DTLS timeouts. (Table 5-4.3)	New and Existing	С	Nov-21	Apr-23
LLDP Management Object Correction (published in PUB00346R0 in June 2021)	2	1.29	 Definition correction to LLDP Enable attribute 1 for both LLDP Enable Array Length and LLDP Enable Array fields. Access Rule of MsgTxHold attribute 3 was changed from Get to Set. 	New and Existing	М	Apr-21	Apr-21
LLDP Date Extension	2	1.29	 LLDP enforcement date was extended from December 2021 to May 2022. Clarify the LLDP implementation requirements: a device containing bridge(s) or implementing In-Cabinet Profile must support both LLDP transmission and reception; otherwise supporting LLDP transmission is required but LLDP reception support is optional. (Section 9-8.1) 	New and Existing	м	Nov-21	May-22
Electronic Key Segment for IO-Link Device	7C	1.02	 The Electronic Key Compatibility bit 7 is moved from Minor Revision byte to Major Revision byte. (Apendix C-2) In the Revision attribute 4 of Identity Object of the Virtual IO-Link Device, Major Revision bits 0-3 shall be IO-Link Protocol Minor Revision, bits 4-6 shall be IO-Link Protocol Major Revision. Minor Revision filed shall be upper 8 bits of the IO-Link Device ID. (Section 5-2.2.3) 		C	Nov-21	Nov-21

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Time Sync Object Attribute Clarifications	1	3.30	 Some instance attributes of Time Sync Object changed data types but no data length change. Time Sync Object is at revision 5 which has a new conditional Associated Interface Labels attribute 31. Associated Interface Objects attribute 29 description is also calarified. 	New and Existing	С	Apr-21	Apr-21
Process Device Diagnostics Object Updates	1	3.30	 Process Device Diagnostic Object Revision 3 is required. (Table 5B-19.5) A required Supported Profile Diagnostics attribute 17 was added. (Table 5B-19.6) 	New and Existing	С	Apr-21	Apr-21
In-Cabinet EtherNet-IP Profile	2	1.27	 A required EtherNet/IP Usage Item in ListIdentity response for devices implementing the In-Cabinet Usage profile. (Table 2-4.6) Two conditional attributes were added to Ethernet Link Object which are required for In-Cabinet Usage Profile. (Table 5-5.3) New Select Link Link Object, In-Cabinet Actual Topology Object and In-Cabinet Commissioning Object were added. (Section 5-17, 5-18 & 5-19) LLDP Data Table Object and two new attributes are required for In-Cabinet Profile Gateway/Router devices. (Table 5-16.3) New required LLDP TLVs for In-Cabinet Profile Gateways Nodes and End Nodes. (Section 9-8.3) 	New	C	Apr-21	Apr-21
Active Certificate Deletion Behavior	8	1.12	Added behavior specification about deletation of an active device certificate. (Section 5-4.4.6 and 5-4.9)	New and Existing	С	Apr-21	Apr-22
Constrained CIP Security	8	1.12	 Added a ligthweight Constrained CIP Security Profile for resource-constrained devices. (Table 1-3.2) Defined a User Authentication/Authorization Proxy scheme for resource-constrained devices and CIP Security Object is updated to support this new prpofile. (Section 2-6 and section 5-3.4) Added two new required Pre-Shared Key Cipher Suites. (Table 3-5.5) Updated EtherNet/IP Security Object to revision 6 to support multiple PSKs needed by Constrained CIP Security Profile. (Section 5-4.3 and 5-4.4) 	New	С	Apr-21	Apr-21
Update EST Service Name	8	1.12	Request CIP Endpoints to look for EST server _est-ciptcp service instead of _esttcp service for CIP certificates. (Section 4-3.4.3.2.1)	New and Existing	С	Apr-21	Apr-21
Send Receive Fragment Requirement	8	1.12	Ethernet/IP devices implemented EtherNet/IP Seucirty Profiles are required to support Send_Receive_Fragment service, Pull Model and File Object. (Table 8-2.1)	New and Existing	С	Apr-21	Apr-21
Certificate Signing Request with Subject Alt Name	8	1.12	 Added Subject Alternative Name to Create_CSR service which updated Certificate Management Object to revision 2. (Table 5-5.15). Conformant CIP Security devices shall be updated to support the new service parameter. A optional Check Subject Alternative Name attribute was added to EtherNet/IP Security Object. (Table 5-4.3) 	New and Existing	С	Apr-21	Nov-22
Requirement for Output Ownership	5	2.22	OCPUNID is required only for connection points that directly control 'safety outputs' within an 'output device'. (Section F-3.10.1.4) (Section 5-4.2)	New and Existing	С	Apr-21	Apr-21
Addition of base format deprecation grace period	5	2.22	From 1/1/2021 to 1/1/2022, target-only device(s) seeking a new Declaration of Conformity from ODVA without base format deprecation will be given a conformance warning. After 1/1/2022 target-only device(s) which have not deprecated the base format will not be able to obtain a new Declaration of Conformity from ODVA.	New and Existing	С	Apr-21	Apr-21

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
CIP Security Session ID	1	3.29	The User Authentication Session ID Network Segment is added (Section C-1.4.3) to support CIP Security User Authenication Profile.	New and Existing	С	Nov-20	Nov-20
Process Device Diagnostics Object Updates	1	3.29	 Process Device Diagnostic Object Revision 2 is required. (Table 5B-19.4) A Optional Recommended Action attribute 11 was added. (Table 5B-19.6) Class attribute 16 User Diagnostic Groups was changed from Required to Optional. (Table 5B-19.1) 	New and Existing	С	Nov-20	Nov-20
Serial Number E-key Correction	1	3.29	New status code 0x13A (Serial Number Mismatch) (Table 3-5.34)(Table 5A-3.33)	New and Existing	С	Nov-20	Nov-20
Identity Object Instance Level GAA Response	1	3.29	 Identity Object Revision 2 is defined. For devices support revision greater than 1, GAA response shall include attribute 14, 19-22 if those attributes are implemented. (Table 5A-2.11) Issue Advisory for devices only support revision 1. 	New	С	Nov-20	Nov-20
CIP Security User Authentication Profile	8	1.11	 The newly added CIP Secuirty User Authentication Profile will provide user level authentiation and basic authorization. (Table 1-3.2) Added three new CIP objects: Authority Object, Password Authenticator Object and Certificate Authenticator Object. (section 5-2) A updated format of CIP Security Item in ListIdentity response. (Table 3-5.1) CIP Security Object is in Revision 4 and add new Required Security Profiles Configured instance attribute 3. (Table 5-3.1 and Table 5-3.2) 	New	С	Nov-20	Apr-22
Objects Cleanup	8	1.11	 Kick_Timer service of CIP Security Object shall only be accepted in Configuration In Progresss state otherwise shall return status 0x0C (section 5-3.7.2) When Delete service is used to delete an static instance, status code 0x2D shall be returned, not status 0x0C. (section 5-5.5.2) Kick_Timer service of EtherNet/IP Security Object shall only be accepted in Configuration In Progresss state otherwise shall return status 0x0C (section 5-4.7.2) 	New and Existing	Μ	Nov-20	Nov-21
Modification of Max Fault Count	5	2.21	 The Max_Fault_Number parameter in Safety Open is changed from a range to a constant 2. (section 2-6.1) The Max Fault Number attribute 22 is changed to have a fixed value 2 and Get only. (Table 5-6.2) The Max_Fault_Number field of Safety Network Segment is changed to a fixed value 2. (Table C-5.1) TST112, TST117, TST9, TST118, TST10, TST119, TST95 are all updated to use Max_Fault_Number = 2 (F-3.6.2, F3.9.2, F-3.4.2, F-4.11) 	New and Existing	Μ	Nov-20	Nov-20

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Unit Code cleanup	1	3.28	Update Symbols for several Engeering Units, such as x2609, x260A, x261A, x2621, etc. (Section D-2.7, D-2.25)	New and Existing	М	Apr-20	Apr-20
Member List Clarifications	1	3.28	 Assembly Object instance attribute 1 and 2 clarification (Table 5A-5.4). Clarify that the padding between Connection Point members shall be represented as null members in the Connection Point Member list. (section 4.8.1) Correct Standard Network Diagnostic Assmbly Content and Ordering. (Table 5A-5.15) Explain how to handle padding in Get_Connection_Point_Member_List service. (section A-4.23.1) 	New and Existing	C	Apr-20	Apr-20
CIP Security Object Reset	8	1.10	Specify CIP Security Object Revision 3 which adds a Required Reset service. (Table 5-3.5)	New and Existing	М	Apr-20	Apr-21
DTLS Extensions for UDP-Only Transport	8	1.10	 For UDP-only EtherNet/IP security device, DTLS is used for all CIP communications sent in a CIP Security context. (Section 3-2.1) New StartDTLS command (section 3-5.3.2) Specify EtherNet/IP Security Object Revision 5 which adds new UPD-only Policy attribute. (Table 5-4.3) 	New	С	Apr-20	Apr-20
UDP-Only EtherNetIP for Constrained Devices	2	1.26	 Specify requirements for a UDP-only EtherNet/IP solution which causes changes in handling of Encapsulation commands and UCMM. (Table 2-3.2) ListIdentiy reply has one new EtherNet/IP Capability Item. (Table 2-4.5, Table 2-6.3) Introduce the EtherNet/IP Transports Application Profile. (Chapter 11) TCP/IP Interface Object Encapsulation Inactivity Timeout attribute is not allowed for UDP-Only EtherNet/IP Transport Profile. (Table 5-4.3) 	New	С	Apr-20	Apr-20
Unit Code cleanup	7B	1.2	Update Symbols of several Engeering Units for HART devices. (section D-1.1)	New and Existing	м	Apr-20	Apr-20
Base Format Deprecation	5	2.20	Remove the requirement to implement and test the Base Format. (Table 2-1.3)	New and Existing	м	Apr-20	Apr-20
Test TST42, TST43 and TST44 Corrections	5	2.20	Update TST42, TST43 and TST44 to accept correct error code. (F-3.10.1.2, F-3.10.1.3,	New and Existing	М	Apr-20	Nov-21
Cleanup Configuration Procedure Guidelines	5	2.20	Remove classs 3 connection requirement for SNCT configuration data transfer so SRS138 was removed from TST55. (F-3.11.5.5)	New	М	Apr-20	Nov-21
Switch change detect	5	2.20	Remove the requirement for a background test of the switches in safety devices so FRS350, FRS351 and FRS 354 were removed from TST50 (F-3.11.2); FRS350 and RSR364 were remvoed from TST108 (F-3.11.3).	New	М	Apr-20	Apr-20

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
File Object Clarifications & Extensions	1	3.27	 Specify File Object Revision 3 which has new attribute 12 and different behaivor (Table 5A-42.27) than rev 1 or 2. CIP Security device is required to support revision 3. New Optional Encoding parameter to Create service (Table 5A-42.10). 	New and Existing	С	Dec-19	Jun-21
Assembly Object Class Revision Attribute clarification	1	3.27	Assembly Object Revision attribute value can be either 02 or 03 (Table 5A-5.3).	New and Existing	С	Dec-19	Dec-19
Orphan Certificate Cleanup	8	1.9	 Specify CIP Security Object Revision 2 which adds a Required Object_Cleanup service (Table 5-3.9). Update Apply Behavior Flag parameter for Apply_Config service of EtherNet/IP Security Object (Table 5-4.12). 	New and Existing	С	Dec-19	May-19
EIPSO Reset Condition	8	1.9	Reset service must be sent over a TLS session conditional on the EtherNet/IP Security Object being in the configured state. (Section 5-4.5.1)	New and Existing	С	Dec-19	Dec-19
EIPSO State Addition	8	1.9	Specify EtherNet/Ip Security Object Revision 4, added new Pull Model Disabled state and changed Atrribute #13 to Get only. Stte Event Matrix Table 5-14.14 was updated with the new state.	New and Existing	С	Dec-19	Dec-19
LLDP	2	1.25	 LLDP Management Object (0x109) and LLDP Data Table Object (0x10A) definition are added (Section 5-15 and Section 5-16). Specify ODVA specific implementation of the Link Layer Discovery Protocol (LLDP) (section 9-8). If LLDP protocol is supported, LLDP Management Object shall be implemented. If receive mode is implemented, either LLDP Data Table Object or SNMP shall be implemented. EtherNet/IP Devices undergoing certification for the first time and multi-port devices receiving an update that adds CIP functionality are required to implement LLDP protocol. 	New and Existing	Μ	Dec-19	Dec-21

Scope of Products Scope of Publish Effective Topic Volume Edition Description Impacted Change Date Date 1. Assembly Object Revision attribute should be 3, 1 and 2 are only allowed for Static Assemblies (Table 5A-5.3). New Conditional attribute Member List Signature (Table 5A-5.4). Standard Network Diagnostic Assy 1 3.26 New and Existing С Apr-19 Nov-20 2. New Conditional Get Connection Point Member List service for Connection Manager, Time Sync Object (Table 3-5.3, Table 5B-2.17). 1. Reset service is only required for instgance 1. Identity Object Reset Service Clarification 2. Devices that reset the whole device if a Reset has been directed to Instances greater than 1 will be non-С Apr-20 1 3.26 New and Existing Apr-19 conformant. EtherNet/IP Security Object Revision updates to 3. New required attribute DTLS Timeout is added for CIP DTLS Timeout Enhancement 8 1.8 New and Existing С Apr-19 Apr-19 Security device. After a device's CIP Security Object has attained the CONFIGURED state configuration changes must only be accepted if the changes are made over a CIP Security connection for File Object, TCP/IP Object and Requiring CIP Security for Services 8 1.8 New and Existing С Apr-19 May-19 Ethernet Link Object (Section 4-3.1.3). CMO State Machine Clarification Verify Certificate service clarification and CMO State clarification. (Table 5-5.17 and Table 5-5.18) New and Existing 8 1.8 С Apr-19 Apr-19 Add new Conditional attributes and services to Safety Dual Feedback Channel Object for multiport safety 5 Feedback Ratio 2.18 New and Existing С Apr-19 Apr-19 devices. (Section 5-4)

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
Common Object Class EDS Correction	1	3 75	Object_Name and Object_Class_Code keywords are required in the [Assembly], [Parameter], [Group] section of eds file if such object exists in the device.(Table 7-3.32, Table 7-3.5, Table 7-3.29.)	New and Existing	М	Nov-18	Apr-19
HART Hooks	1	3.25	New required attributes are added to Identity Object for HART devices (Table 5A-2.3)	New	С	Nov-18	Nov-18
File Instance Clear_File and Save Params	1	3.25	Clear_File service shall not clear File Save Parameter. (Section 5A-42.5.7)	New and Existing	М	Nov-18	Nov-18
STIME correction	1	3.25	STIME shall be data type ULINT not LINT.	New and Existing	М	Nov-18	Nov-18
Remove Integrity Profile	8	2.17	Integrity Profile is obsolete for CIP Security device.	New and Existing	М	Nov-18	Nov-18

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
System Time Definition	1	3.24	Improve elementary data type for System Time (STIME) (Table C2.1, Section C-3.3, Section 7-3.5.1.12)	New and Existing	М	Apr-18	Apr-18
Invalid Connection Size Status Code	1	3.24	Allow an exception for CIP-Modbus translators to use Status Code 0x109 (Table 3-5.33)	New and Existing	М	Apr-18	Apr-18
Pull Model	8	1.6	Pull Model is a new mandatory capability of CIP Security devices. (Section 4-3, 5-4, 5-5, 6-5.3)	New and Existing	С	Apr-18	May-21
EIP Security Object IF Linkage	8	1.6	Each CIP Security device with more than one IP address shall support the Port Object and the Associated Communication Objects attribute. (Section 5-4.1)	New and Existing	С	Apr-18	Apr-18
Multiport Safety Devices	5	2.17	Add new Required attributes and services of Safety Supervisor Object for multiport safety devices. (Section 5- 4)	New and Existing	С	Apr-18	Apr-18

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
PTP_Leap_Seconds_Attribute	1	3.23	 a. Revision Class attribute can be 3 or 4 (required for Master capabple device). (Section 5B-2.3) b. New conditional attribute 30. (Section 5B-2.4) 	New and Existing	С	Nov-17	May-19
Port Type 0 Associated Communication Objects Issue	1	323	a. Port Type and associated objects classification. (Table 3-7.4) b. Associated Communication Object attribute clarification. (Section 3-7.2.1.9)	New and Existing	С	Nov-17	Nov-17
CIP Sync over PRP	1	3.23	A new PTP profile for PRP (Table 5B-2.20)	New and Existing	С	Nov-17	Nov-17
Connection Manager Error Codes Updates	1	3.23	New Connection Manager Error Codes (Table 3-5.33)	New and Existing	С	Nov-17	Nov-17
Get-Set_Attribute_List Clarifications	1	3.23	Clarification of Get/Set_Attribute_List service (Section A-4.3 and Section A-4.4)	New and Existing	С	Nov-17	Nov-18
Commissioning Updates	8	1.5	Enhanced commissioning requirements. (Section 4-3 and section 5-3)	New and Existing	С	Nov-17	Nov-17
Enhance Certificate Trust	8	1.5	a. New required Trusted Identities attribute of EtherNet/IP Security Object (Section 5-4.4) b. Clarification of Certificate Management Object (Section 5-5.4)	New and Existing	С	Nov-17	Nov-17
Correct CIP Security Object Get Attr All	8	1.5	Correct error in CIP Security Object instance level Get_Attribute_All response layout (Table 5-3.8)	New and Existing	С	Nov-17	Nov-17
Secure CL3 and Non-Secure CL1 Clarification	8	15	Guideline on how to open non-secure Class 0/1 connection via secure UCMM or Class 3 connection (Section 3- 5.7.2.4)	New and Existing	с	Nov-17	May-18

Торіс	Volume	Edition	Description	Scope of Products Impacted	Scope of Change	Publish Date	Effective Date
File Object Enhancements	1	3.22	 a. Revision Class attribute can be 1 or 2. (Section 5A-42.2) b. Changed definition of the File Save Parameters attribute. (Section 5A-42.2.1.8) c. State Event Matrix change for Download Transfer, First-and-last and Upload_Transfer event. (Table 5A-42.26) 	New and Existing	С	Apr-17	Nov-17
PTP port number association	1	3.22	 a. Associated Interface Objects attribute is added to Time Sync Object to declare the PTP port number association. (Table 5B-2-3) b. [AssociatedInterfaceObjects] Entry Keyword is added to eds file. (Section 7-3.6.6.1) 	Only New	С	Apr-17	Nov-17
Missing Item Count	8	1.4	Added Item Count to CPF Item for Unconnected Message over UDP for DTLS. (Table 3-5.4)	New and Existing	М	Apr-17	Apr-17
Null Fwd Open Clarification	8	1.4	Specify how a Null ForwardOpen should be sent in the presence of CIP Security. (Section 3-7)	New and Existing	С	Apr-17	Apr-17
Cert Format Clarification	8	1.4	Certificate Encodings Flag attribute and Certificate Encoding attribute are added to Certificate Management Object to specify certificate format. (Section 5-5.3.3 and Section 5-5.4.1)	New and Existing	М	Apr-17	Apr-17
PSK Format Clarification	8	1.4	Specify encoding format for Pre-shared keys. (Section 5-4.4.5)	New and Existing	М	Apr-17	Apr-17
MCAO_Not_Required	9	1.1	A Motion Control Axis Object or a vendor specific equivalent construct needs to be in CIP Motion Controller. (Section 1-2.2)	New and Existing	С	Apr-17	Apr-17
Enhancements for PRP HSR	2	1.23	 a. PRP/HSR Nodes Table with Active Status attribute is added to PRP/HSR Table Object. (Section 5-14.3.3.1) b. Get_Member service is now Required for PRP/HSR Table Object. (Table 5-14.4) c. Diagnostic attributes 17 - 20 are added to PRP/HSR Protocol Object. (Table 5-13.3) 	New and Existing	С	Apr-17	Nov-17